

Features & Benefits:

- Drive 1" to 3" screws with this integrated system, no awkward attachments
- Adjustable, accurate depth control for countersinking, no raised screw heads
- Telescopic extension handle for stand-up operation, relieves operator fatigue
- 150 screw coil magazine, less time spent reloading
- Industrial strength for the professional contractor
- Rubber nose piece, prevents damage to floor or deck surfaces
- Bits are double-ended, change bits in seconds without special tools



The Professional Way To Drive Screws!



One Tool Does It All! Underlayment Cement, Backer Board, Sub-Floor, Decks and Docks

Muro's Speed Driver, model FDVL41 is the only Coil Auto Feed Screw Driving System in the industry. This tool can drive screws from 1" to 3" in length providing the versatility to meet all your construction fastening needs. This high performance and durable tool is the choice of professional contractors throughout the world. Get the Muro Advantage today.

Specifications

Speed: 2900 RPM or 2400 RPM Voltage: 115V Current: 5.0A Screw Range: 1" to 3" Accessories: Palm Handle, Telescopic Extension Handle Driver Bits - Double ended, last twice as long: SQR27114 (Square Drive #2), PHL27114 (Phillips Drive #2), TX207114 (Torx Drive #20), TX257114 (Torx Drive #25)

VISTOPE® Collated Screw Coils - FDVL41



Recess	Thread	Coating	Available Sizes	Application
Phillips	Fine	Black Phosphate	1, 1-1/4, 1-5/8, 2, 2-1/4, 2-1/2, 3	Drywall or wood to light gauge steel
Phillips	Coarse	Black Phosphate	1, 1-1/4, 1-5/8, 2, 2-1/4, 2-1/2	Drywall or wood to wood
Phillips	Self Drill	Bright Zinc	1-1/4, 1-5/8, 2, 2-3/8, 3	Drywall or wood to heavy gauge steel

Sub Floor & Underlayment Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Yellow Zinc	1, 1-1/4	Wood to wood
Square	Fast Pitch Twin	Yellow Zinc	1-1/2, 1-3/4, 2, 2-1/2, 3	Wood to wood
Phillips	Coarse	Yellow Zinc	1-1/4, 1-1/2, 1-3/4, 2, 2-1/2	Wood to wood
Square	Self Drill	Bright Zinc	1-1/4, 1-1/2, 2	Wood To Steel
Square	Hi-Lo	Yellow Zinc	1-1/4	Wood To wood

Cement Board Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Silver Ceramic	1-1/4, 1-3/4	Cement backer board to wood
Square	Self Drill	Silver Ceramic	1-5/8	Cement backer board to steel

Deck & Dock Screws

Recess	Thread	Coating	Available Sizes	Application		
Square	Coarse	Green Epoxy	1-1/4, 1-1/2, 1-3/4	Decking to wood		
Square	Fast Pitch Twin	Green Epoxy	2, 2-1/2, 3	Decking to wood		
Square	Fast Pitch Twin	Gray Epoxy	2-1/2, 3	Decking to wood		
Square	Coarse	Brown Epoxy	2-1/2, 3	Decking to wood		
Square	Coarse	305 Stainless	1-1/8, 1-3/4, 2, 2-1/2, 3	Decking to wood		
Square	Coarse	316 Stainless	2, 2-1/2, 3	Decking to wood		

Composite Deck Screws - Shroomless Fastening for Composite Decking

Recess	Thread	Coating	Available Sizes	Application
Torx	Torx Shroomless Tan, Gray & Brown Ceramic		2-1/2	Composite decking to wood
Torx	orx Shroomless Stainless Steel		2-1/2, 3	Composite decking to wood

Trim Head Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Silver Ceramic	2-1/4, 3	Composite decking or wood to wood
Square	Coarse	Stainless Steel	2-1/2, 3	Composite decking or wood to wood

Ejector Hardwood Screws – Fastens Ipe, Cumaru and others without pre-drilling

Recess	Thread	Coating	Available Sizes	Application
Square/Torx	Ejector	305 Stainless	1-1/2, 2, 2-1/2, 3	Exotic hardwood decking to wood







